	SAFETY DATA	SHEET (SDS)		
Tri-State Cast Technologies Co., Inc.	YELLOW and CASTINGS	I LEADED YE	LLOW BRASS ALLOY	
	(Cu-Zn & Cu-	Zn-Pb Alloys	)	
Meets the Requirements of OSHA Standard 29 CFR	SDS SC-000-	021 Rev 12		
1910.1200 Hazard Communication and EPA Supplier Notification Requirements under Section 313 of the	DATE ISSUED			
Emergency Planning and Community Right-to-Know Act. © 2015 American Foundry Society, Inc.	01/15			
SECTION 1—PRODUCT IDEN			ATION	
PRODUCT NAME YELLOW and LEADED YELLOW BRASS (Cu-Zn & Cu-Zn-Pb Alloys)	ALLOY CAST	INGS		
OTHER DESIGNATIONS: Copper Alloy Specification No's Unified UNS ALLOY DESIGNATIONS:	Numbering System (UI	NS)		
C85200 C85700				
C85400 C85800				
C85500				
PRODUCT IDENTIFICATION (Label Identifier)				
MANUFACTURER'S NAME	STREET ADDRESS			
EMERGENCY TELEPHONE NO.	MAILING ADDRESS			
TELEPHONE NO.     CITY, STATE, ZIP CODE, COUNTRY		COUNTRY		
FAX NO.	E-MAIL AD	DRESS/WEBSI	ſE	
RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE				
Solid casting; no restrictions				
SECTION 2—HAZARD IDENTIFICATION				
CLASSIFICATION				
Castings are metallic articles that do not present hazards in their original form.				
<ul> <li>OTHER INFORMATION</li> <li>1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.</li> </ul>				
2. Fumes from hot processes may contain other				
generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 for further information.				
SECTION 3—COMPOSITION/INFORMATION ON INGREDIENTS				
CHEMICAL NAME/COMMON NAME/SYNONYM Wt % CAS NUMBER				
Cobalt (Co) Metal	<0	).1–1.0	7440-48-4	
Copper (Cu) Metal	57	.0–75.0	7440-50-8	
Lead (Pb) Metal	0.:	20–3.8	7439-92-1	
Nickel (Ni) Metal	<0	).1–1.0	7440-02-0	
Tin (Sn) Metal	0	.5–2.0	7440-31-5	
Zinc (Zn) Metal	20	.0–41.0	7440-66-6	
Vellow and Leaded Vellow Brass Alloy Castings	SDS SC-000-021 Rev 12	·	Page 1 of 6	

### SECTION 4—FIRST AID MEASURES

EYE CONTACT: Not applicable

**SKIN CONTACT:** No special requirements

**INGESTION:** Not applicable

**INHALATION:** Not applicable

## **SECTION 5—FIREFIGHTING MEASURES**

## FLAMMABLE PROPERTIES: Not applicable

EXTINGUISHING MEDIA: Not applicable

**PROTECTION OF FIREFIGHTERS:** Not applicable

## SECTION 6—ACCIDENTAL RELEASE MEASURES

Not applicable

# SECTION 7—HANDLING & STORAGE

## RECOMMENDED STORAGE

No special requirements

### **PROCEDURES FOR HANDLING**

Proper hand and foot protection is recommended.

## SECTION 8—EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS

None Required. There are no health hazards from castings in solid form.

SUBSTANCE	ACGIH TLV mg/m <sup>3</sup>	OSHA PEL mg/m <sup>3</sup>
Cobalt (Co) Metal	0.02	0.1
Copper (Cu) Metal	1	1
Lead (Pb) Metal	0.5	30μg/m <sup>3</sup> AL 50μg/m <sup>3</sup> PEL (See 29CFR1910.1025)
Nickel (Ni) Metal	1.5 (l)	1
Tin (Sn) Metal	2	2
Zinc (Zn) Metal	N/E	N/E

#### SUPPLEMENTAL INFORMATION

Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.

Fumes from hot processes may contain other compounds with different exposure limits than those listed herein.

Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Exposure limits for the most common contaminants are offered as reference. Please consult a competent person for guidance on exposure assessment and controls.

SUBSTANCE	ACGIH TLV mg/m <sup>3</sup>	OSHA PEL mg/m <sup>3</sup>
Cobalt (Co) Metal		
Metal Dust and Fume	N/E	0.1
Elemental and Inorganic Compounds	0.02	N/E

Fume (Cu)	0.2	0.1
Dusts and Mists (Cu)	1	1
Lead Compounds		
Inorganic Compounds (Pb)	0.05	30μg/m³ AL 50μg/m³ PEL (See 29CFR 1910.1025
Nickel Compounds (Ni)		
Insoluble, Inorganic Compounds	0.2 (I)	1
Soluble, Inorganic Compounds	0.1 (l)	1
Nickel Oxide	0.2 (l)	1
Tin Oxide (Sn)	2	N/E
Zinc Compounds (Zn)		
Zinc Oxide Total Dust	N/E	15
Zinc Oxide Respirable Dust	2 / 10 STEL	5
Zinc Oxide Fume	N/E	5
PEL = Permissible Exposure Limit / OSHA AL = Action Level / OSHA		
mg/m <sup>3</sup> = milligrams per cubic meter μg/m <sup>3</sup> = micrograms per cubic meter		
$\mu g/m^3 =$ micrograms per cubic meter		
μg/m <sup>3</sup> = micrograms per cubic meter <b>PERSONAL PROTECTION</b> Proper hand and foot protection is recommended.	L & CHEMICAL PROPERTIES	
μg/m <sup>3</sup> = micrograms per cubic meter PERSONAL PROTECTION Proper hand and foot protection is recommended. SECTION 9—PHYSICA APPEARANCE/PHYSICAL STATE	L & CHEMICAL PROPERTIES	
μg/m <sup>3</sup> = micrograms per cubic meter <b>PERSONAL PROTECTION</b> Proper hand and foot protection is recommended. <b>SECTION 9—PHYSICA</b>	L & CHEMICAL PROPERTIES	
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         Section 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color	VAPOR DENSITY	
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         Section 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color		
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         SECTION 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color         ODOR/ODOR THRESHOLD         None         MELTING POINT/FREEZING POINT	VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de	• ·
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         Section 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color         ODOR/ODOR THRESHOLD         None         MELTING POINT/FREEZING POINT         Approximately 1085°C (1984°F) for copper	VAPOR DENSITY Not applicable	• •
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION       Proper hand and foot protection is recommended.         Section 9—PHYSICA       Section 9—PHYSICA         APPEARANCE/PHYSICAL STATE       Solid, Orange-red in color         ODOR/ODOR THRESHOLD       None         MELTING POINT/FREEZING POINT	VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de	• •
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION       Proper hand and foot protection is recommended.         Section 9—PHYSICA       Section 9—PHYSICA         APPEARANCE/PHYSICAL STATE       Solid, Orange-red in color         ODOR/ODOR THRESHOLD       None         MELTING POINT/FREEZING POINT       Approximately 1085°C (1984°F) for copper         Melting point of copper-zinc alloy (20-41% zinc) is approximately 900-1000°C (1652-1832°F)	VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative de	• •
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         SECTION 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color         ODOR/ODOR THRESHOLD         None         MELTING POINT/FREEZING POINT         Approximately 1085°C (1984°F) for copper         Melting point of copper-zinc alloy (20-41% zinc) is	VAPOR DENSITY Not applicable SPECIFIC GRAVITY (relative den 8.96 g/cm <sup>3</sup> for copper (water = 1)	• ·
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         SECTION 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color         ODOR/ODOR THRESHOLD         None         MELTING POINT/FREEZING POINT         Approximately 1085°C (1984°F) for copper         Melting point of copper-zinc alloy (20-41% zinc) is approximately 900-1000°C (1652-1832°F)         BOILING POINT	VAPOR DENSITY         Not applicable         SPECIFIC GRAVITY (relative der         8.96 g/cm <sup>3</sup> for copper (water = 1)         VAPOR PRESSURE	• •
μg/m³ =       micrograms per cubic meter         PERSONAL PROTECTION       Proper hand and foot protection is recommended.         Section 9—PHYSICA       Section 9—PHYSICA         APPEARANCE/PHYSICAL STATE       Solid, Orange-red in color         ODOR/ODOR THRESHOLD       None         MELTING POINT/FREEZING POINT       Approximately 1085°C (1984°F) for copper         Melting point of copper-zinc alloy (20-41% zinc) is approximately 900-1000°C (1652-1832°F)         BOILING POINT         2562°C (4644°F) for copper	VAPOR DENSITY         Not applicable         SPECIFIC GRAVITY (relative derection of the second of th	• •
μg/m³ = micrograms per cubic meter         PERSONAL PROTECTION         Proper hand and foot protection is recommended.         SECTION 9—PHYSICA         APPEARANCE/PHYSICAL STATE         Solid, Orange-red in color         ODOR/ODOR THRESHOLD         None         MELTING POINT/FREEZING POINT         Approximately 1085°C (1984°F) for copper         Melting point of copper-zinc alloy (20-41% zinc) is approximately 900-1000°C (1652-1832°F)         BOILING POINT         2562°C (4644°F) for copper         FLASH POINT	VAPOR DENSITY         Not applicable         SPECIFIC GRAVITY (relative der         8.96 g/cm³ for copper (water = 1)         VAPOR PRESSURE         Not applicable         EVAPORATION RATE	• •

Not flammable for castings in solid form

Not applicable for castings in solid form

UPPER AND LOWER FLAMMABILITY LIMITS

рΗ

Insoluble

Not applicable

AUTO IGNITION TEMPERATURE Not applicable		VISCOSITY Not applicable		
DECOMPOSITION TEMPERATURE		PARTITION COEFFICIENT		
Not applicable Not applicable SECTION 10—STABILITY & REACTIVITY			TV	
			EACTIVI	I Y
CHEMICAL STABILITY: Castings in solid form	are stable	•		
CONDITIONS TO AVOID: None				
REACTIVITY: Not reactive				
HAZARDOUS DECOMPOSITION PRODUCTS	5	HAZARDOUS POLYMERIZATION		YMERIZATION
None	Not applicable SECTION 11—TOXICOLOGICAL INFORMATION			
	-TOXICOI	LOGICAL	INFORM	ATION
POTENTIAL HEALTH EFFECTS				
EYE CONTACT: None				
SKIN: None				
INGESTION: None				
INHALATION: None	<b>.</b>			
	1	1		
INGREDIENT	OSHA	NTP	IARC	TARGET ORGAN(S)
Cobalt and Compounds	NL	NL-	2B	Lung
Lead and Inorganic Compounds	NL	R	2A	Lung, Stomach, Liver, Kidney
Nickel Metal	NL	K	2B	Lung, Nasal passages
<ul> <li>K = Known to be a Human Carcinogen</li> <li>R = Reasonably Anticipated to be a Human Carcinogen (RAHC)</li> <li>IARC—International Agency for Research on Cancer</li> <li>1 = Carcinogenic to Humans</li> <li>2A = Probably Carcinogenic to Humans</li> <li>2B = Possibly Carcinogenic to Humans</li> <li>3 = Unclassifiable as to Carcinogenicity in Humans</li> <li>4 = Probably not Carcinogenic to Humans</li> </ul>				
Other NL = Not Listed				
SECTION 12	2—ECOLO	DGICAL IN	FORMA	ΠΟΝ
ECOTOXICITY PERSISTENCE AND DEGRADABILITY		ND DEGRADABILITY		
Not applicable Not applica		licable		
BIOACCUMULATION POTENTIAL MOBILITY IN SOIL		L		
Not applicable Not applicable				
Not applicable				
OTHER ADVERSE EFFECTS Not applicable SECTION 13 Recover or recycle if possible. Dispose of accorrection actions, welding, etc. may be classified as	ording to fe	ederal, stat	te and loc	al regulations. Dust collected from
Not applicable SECTION 13 Recover or recycle if possible. Dispose of acc	ording to fe a hazardou	ederal, stat us waste. (	te and loc Consult fe	al regulations. Dust collected from deral, state and local regulations.
Not applicable SECTION 13 Recover or recycle if possible. Dispose of according machining, welding, etc. may be classified as	ording to fe a hazardou 4—TRAN	ederal, stat us waste. ( SPORT IN	te and loc Consult fe FORMAT N TRANS TDG)	al regulations. Dust collected from deral, state and local regulations.

UN SHIPPING NAME	UN NUMBER	
Not regulated	Not regulated	
TRANSPORT HAZARD CLASS	PACKING GROUP	
Not regulated	Not regulated	
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?	
None	No	
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION	
Not applicable	Not applicable	
SECTION 15—REGL	JLATORY INFORMATION	
US-OSHA (Hazard Communication Standard) References: 29 CFR 1910.1200 Hazard Communicat A finished casting is an article as defined 29 CFR 1910.1000 Air Contaminants 29CFR1910.1025 Lead		
Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as cobalt, copper, lead, nickel, tin, zinc and silica.		
US-EPA (Toxic Substances Control Act–TSCA)		
All components of these products are on the TSCA in	ventory list or are excluded from listing.	
US-EPA (SARA Title III) Belasses to the environment of Cobalt, Copper, Lea	d, Nickel, and Zinc (fume or dust) may be subject to	
	nd Amendments and Reauthorization Act of 1986 and 40	
CANADA-WHMIS (Workplace Hazardous Materials In	formation System)	
• •	criteria of the Controlled Product Regulations (CPR) and the	
CANADA DSL (Domestic Substances List) Inventory	Status	
All components of these products are on the DSL Inve	entory.	
CEPA (Canadian Environmental Protection Act)		
Lead is on the Toxic Substances List.		
EINECS No. (European Inventory of Existing Comme	rcial Chemical Substances)	
All components of these products are on the EINECS list.		
RoHS (Restriction of Certain Hazardous Substances) Compliance		
Castings comply with RoHS		
CALIFORNIA PROPOSITION 65 Compliance		
	Is including nickel which is known to the State of to the State of California to cause birth defects or other ment for the chemical composition of this product. For	
US STATE REGULATORY INFORMATION		
Some of the components listed in Section 3 may be c	overed under specific state regulations.	
SECTION 16—OTHER INFORMATION		
SDS PREPARED BY	DATE	
American Foundry Society, Inc.	01/15	
Occupational Safety & Health Committee (10-Q)		
NOTE	I	
This data and label information is offered in good faith	as typical values and not as a product specification. No The recommended industrial hygiene and safe handling wever, each user should review the recommendations in	

procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

Addendum: Label Information

PRODUCT IDENT	IFIER
---------------	-------

SC-000-021 Rev 12 YELLOW and LEADED YELLOW BRASS ALLOY CASTINGS (Cu-Zn & Cu-Zn-Pb Alloys)

SUPPLIER IDENTIFICATION	HAZARD PICTOGRAMS
Company Name	None*
Street Address	SIGNAL WORD
Mailing Address	None*
City State	
Zip/Postal Code Country	
Emergency Phone Number	
Other Info	
PRECAUTIONARY STATEMENTS	HAZARD STATEMENTS
None*	None*

\*Castings do not present hazards in their original form.

## **OTHER INFORMATION**

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 of the SDS for further information.